

LED FLEXIBLE STRIP TAPE

UL Listed

cULus

CE

Dimmable

50,000+ hrs

IP20

CRI 95+

DEFINITION SERIES: NORMAL BRIGHTNESS

Higher CRI and brightness for true, vibrant color (CRI 95+).


Visual clarity for ambient, accent or task lighting that enhances the design of any space.



SPECIFICATIONS

Input voltage	24V DC
Power	4.4 W/ft
CRI (Ra)	95+
Lumens	300–360 lm/ft
Beam angle	120°
Environment	IP20
Max. continuous run	16.4 ft
Reel length	16.4 ft

DIMENSIONS



Cut length 3.94 in / 100 mm

Width 0.39 in / 10 mm

Thickness 0.079 in / 2 mm

MODEL NUMBER CODE

D

24

NB

XX

4.4

Series

Voltage

Brightness

Color temp

Watts/ft

XX = color temp: 27 = 2700K, 30 = 3000K, 40 = 4000K

COLOR TEMPERATURES AVAILABLE

2700K

D-24NB274.4

Normal Brightness 2700K

3000K

D-24NB304.4

Normal Brightness 3000K

4000K

D-24NB404.4

Normal Brightness 4000K

RECOMMENDED CONNECTORS

PART NUMBER	DESCRIPTION
T-T2P	Tape-to-tape 2-pin connector
T-W2P	Tape-to-wire 2-pin connector
ST-T-W2P	Screw-terminal tape-to-wire 2-pin
HDT-W2P	High-density tape-to-wire 2-pin connector
HDT-T2P	High-density tape-to-tape 2-pin connector

Full connector list: [LL Connector Quick Reference](#).

Evaluated by UL to UL 2108 (Low Voltage Lighting Systems) and CSA-C22.2 No. 250.2 (Lighting Systems).
UL file E529623. Backed by the Lighting Leaf 5-year warranty.

5-YEAR WARRANTY

Specifications may vary with use and are subject to change. See [lightingleaf.com](#) for current data.