

LED FLEXIBLE STRIP TAPE

UL Listed

cULus

CE

Dimmable

50,000+ hrs

IP20

IP67 option

EXTEND SERIES: LONG CONTINUOUS RUNS

Built for continuous long-distance lighting with fewer cut and feed points.

Ideal for crown molding, coves, soffits and long corridors: up to 80 ft continuous on one feed.


Waterproof version available: X-24NB301.5IP67.



SPECIFICATIONS

Input voltage	24V DC
Power	1.5 W/ft
CRI (Ra)	90+
Lumens	110–130 lm/ft
Beam angle	120°
Environment	IP20 (IP67 option)
Max. continuous run	80 ft
Reel length	40 ft

DIMENSIONS



Cut length 1.97 in / 50 mm

Width 0.39 in / 10 mm

Thickness 0.079 in / 2 mm

MODEL NUMBER CODE

X	24	NB	30	1.5
Series	Voltage	Brightness	Color temp	Watts/ft
30 = 3000K				

COLOR TEMPERATURE AVAILABLE

3000K

X-24NB301.5

Normal Brightness 3000K

3000K

X-24NB301.5IP67

IP67, Normal Brightness 3000K

RECOMMENDED CONNECTORS

PART NUMBER	DESCRIPTION
T-T2P	Tape-to-tape 2-pin connector
T-W2P	Tape-to-wire 2-pin connector
ST-T-W2P	Screw-terminal tape-to-wire 2-pin
HDT-W2P	High-density tape-to-wire 2-pin connector
HDT-T2P	High-density tape-to-tape 2-pin connector
WP67-T-T2P	IP67 tape-to-tape 2-pin connector *
WP67-T-W2P	IP67 tape-to-wire 2-pin connector *

* IP67 waterproof connector: rated outdoor for moisture, not submersible. Full connector list: LL Connector Quick Reference.

IP67 VERSION



X-24NB301.5IP67

IP67-rated (encased) LED tape in a fully sealed, matte-finish flexible silicone extrusion. Rated indoor or outdoor for moisture and high humidity (not submersible). Requires separate adhesive to bond to surfaces (not included).

Evaluated by UL to UL 2108 (Low Voltage Lighting Systems) and CSA-C22.2 No. 250.2 (Lighting Systems). UL file E529623. Backed by the Lighting Leaf 5-year warranty.

5-YEAR WARRANTY

Specifications may vary with use and are subject to change. See lightingleaf.com for current data.